

# MOULD INCUBATOR/ BIOCHEMICAL INCUBATOR



SPX-B-ZII / MJX-B-ZII  
Series

Shanghai Boxun Medical Biological Instrument Corp

Add: No. 599 Zhongqiang Road, Maogang Town,  
Songjiang District Shanghai, China

Tel: 021-56980111 Fax: 021-56303876

E-mail: export@shbxyl.com

web: www.sh-bx.com



www.sh-bx.com

## MOULD INCUBATOR/BIOCHEMICAL INCUBATOR >>

### SPX-B-ZII / MJX-B-ZII Series

#### Product Features

- The shell is made of cold-rolling steel with static spray plastics, the working chamber is made of mirror stainless steel, the shelves can be adjusted optionally;
- PMMA II operating system, with over temperature alarm and self-diagnosis function;
- The fan has 6-stage speed regulation, which can meet the different requirements
- 8W fluorescent lamp in working chamber (mould incubator is equipped with 8W UV light);
- Large viewing angle heat preservation vacuum toughened glass is convenient for users to observe;
- Equipped with 220V power socket;
- Frequency conversion refrigeration system, environmental protection refrigerant (R134a), high efficiency, low energy consumption, full temperature continuous frost-free operation;
- Adopt imported compressor unit, low noise, stable performance;
- Power supply recovery function, data will not be lost when power failure and system halted.

Model	SPX-100B-ZII MJX-100B-ZII	SPX-150B-ZII MJX-160B-ZII	SPX-250B-ZII MJX-250B-ZII
Volume [L]	100	150	250
Type	SPX Series Biochemical Incubator/MJX Series Mould Incubator		
Internal Dimensions W×D×H [mm]	500×370×580	500×370×815	500×440×1100
Housing Dimensions W×D×H [mm]	580×570×1070	595×580×1232	615×620×1597
Temp. Range [°C]	5~60	5~60	5~60
Temp. Resolution [°C]	0.1	0.1	0.1
Temp. Fluctuation [°C]	±0.7°C (Heating), ±1°C (Cooling)		
Temp. Uniformity at 37°C [°C]	±1.5		
Power [W]	500	500	670
Timer Range [h]	0-9999min/h		
Number of Shelves (std./max.) [pc]	2/3	3/5	3/7
Load per Shelf [kg]	15		
Net Weight/Gross Weight [kg]	70/82	82/93	100/118
Package Size [mm]	700×660×1260	700×660×1490	730×760×1820